

## ***ELCAN SpecterDR*** **DUAL ROLE OPTICAL SIGHT**

The ELCAN SpecterDR Dual Role Optical Sight represents a revolution in optical sight design. The world's first truly dual field of view combat optical sight, the **SpecterDR** switches instantly from a 4x magnified sight to a 1x CQB sight with the throw of a lever. Unlike zoom sights, the **SpecterDR** offers an optimized optical path and identical eye relief in both 4x and 1x modes.

Depending upon the situation, the user may adjust the sight to illuminate the crosshair or just a brilliant red dot in the center. In 1x mode, the **SpecterDR** has by far the largest field of view in the industry. In 4x mode the **SpecterDR** offers a generous field of view, long eye relief, and ELCAN'S legendary crystal clear image.

The **SpecterDR** offers the best single solution for both CQB and Long Range engagements and is designed to withstand the rigors of modern professional use.





# SpecterDR

Models: **DFOV14-C1** • **DFOV14-C2**



4x mode with red dot illumination



1x mode with red dot illumination

## Specifications

Magnification	1x / 4x
Length	153mm nominal
Width	74mm nominal
Height	78mm nominal
Weight	580g nominal
Reticle	Dual-thickness ballistic crosshair with user-selectable red dot, rangefinder, and 'area fire' circles.
Aiming Dot diameter	1.5 MoA @ 4x, 6 MoA @ 1x
Ballistic correction:	
DFOV14-C1:	CX5395 reticle, 100-600m for 5.56mm carbine, 700-1000m for 5.56mm LMG
DFOV14-C2:	CX5396 reticle, 100-600m for 7.62mm rifle, 700-1000m for 7.62mm LMG
Illumination source	Battery-powered LED
Crosshair illumination	5 settings, night vision compatible
Red Dot illumination	5 settings, night vision compatible
Eye Relief	70 mm
Field of View	26 deg @ 1x, 6.5 deg @ 4x
FoV @1x	48.8 m @ 100 m (146.3 ft @ 100 yds)
FoV @4x	11.4 m @ 100 m (34.2 ft @ 100 yds)
Coaxial alignment	<1.5 MoA between fields
Entrance pupil	28mm
Exit pupil	8mm
Nominal focus	150m @ 4x, 37.5m @ 1x
Fixed focus range	20m to infinity
Battery type	DL 1/3N (3v Lithium)
Battery life	600 hours minimum, 3000 hours average
Exterior finish	Hard-anodized aluminum, gray/black color
Adjustment resolution	0.5 minute of angle
Adjustment range	120 minutes of angle
Base requirement	Mil-Std-1913 'Picatinny Rail'
Attachment	ARMS Levers
Environmental	
Waterproof:	66 ft for 2 hours min
Shockproof:	450 g's